



The AVTV/200A is a Broadband TV class AB Amplifier with rated output power of 250W. It is developed to amplify the Amplitude Modulation signal, in IIIBd VHF.

It is completely manufactured with solid state technology and modular design in one cabinet for mounting in 19" rack with 5 units height, accessible inside by removing the upper and lower panels.

Thanks to its features, the preferable use of the AVTV/200A is as RF Amplifier in small- and medium-size installations.

It can operate without adjustment with power supply from electrical network. The apparatus uses Microcontroller technology for the protection and measurement circuitry, which controls RF output power, SWR, temperature, current and voltage of the RF module.

The I.M.D. is substantially reduced when the Transmitter or the Transposer uses the Linearity Precorrector. A 6-cell Notch Filter is available at the amplifier output to attenuate the intermodulation products levels in the external range.

These specifications are subject to change without notice. Per esigenze tecnico-costrutive ci riserviamo il diritto di apportare varianti ai prodotti, senza preavviso.

TECHNICAL CHARACTERISTICS

RF SECTION

Frequency range III Band

Output power 250W sync.peak

Gain 20dB Input Connector N Female Output Connector N Female

I.M.D. (-8, -10, -16dB) < -54dB (with IF Pre-corrector)

Spurious and harmonics level Better than -60dB

GENERAL

Power supply 110/220 Vac +10% -25% 50Hz-60Hz

Typical power consumption 1300VA
Dimensions 19"- 5U
510x485x265mm

